

## A

Absolute track .....	15
Angular acceleration sensor .....	16; 23
Angular measurement .....	16

## B

Balancing currents .....	24
Ball bearing life time .....	18
Ball bearings .....	18–19
Bandwidth .....	9; 15
Bearings at both ends .....	18
Bearings, insulated .....	19
Brightness regulation .....	9

## C

Cable break .....	24
Cable capacitance .....	12
Cable connection .....	20
Cable gland .....	20
Cable length .....	12
Cable screen .....	20; 24
Cable terminating resistance .....	24
Cable type .....	24
Characteristic impedance .....	12; 24
CE mark .....	21
Combinations .....	18; 23
Common mode rejection ratio .....	24–25
Common shaft .....	16; 20; 23
Commutation signals .....	15
Commutation track .....	15
Converters .....	25
Coupling capacitance .....	25
Coupling faults .....	21
Couplings .....	19; 21
Current limiter of supply .....	17

## D

DC offset .....	11; 14
Declaration of Conformity .....	21
Die-cast housing .....	18
Differential amplifier .....	24–25
Differential input .....	24
Digital-Tachos without bearings .....	19
Direction of rotation detection .....	8
Dissimilarity of sine amplitudes .....	14
Dual channel Digital-Tachos .....	8

## E

Earth connection .....	20; 24
Earth contact .....	19
Earth loops .....	24
Earthing .....	24
Electrical isolation of Digital-Tachos .....	25
Electromagnetic Compatibility (EMC) .....	17
Electronic accessories .....	25
EU declaration of conformance .....	21
EURO-flange® B10 .....	20
Explosion protection .....	20
ExtendedSpeed® angular acceleration sensors ..	16

## F

Ferraris acceleration sensor .....	16
Fibre optic link .....	25
Frequency analysis (FFT) .....	13
Frequency spectrum .....	24

## H

Harmonics .....	13–14
HeavyDuty® technology .....	8; 18
High voltage Transistor Logic (HTL) .....	10
Hollow-shaft .....	13; 19; 21
Housing temperature .....	19
Housing .....	18
HTL technology .....	10
HTL technology, version C .....	11

## I

Incremental disks .....	8
Insulated ball bearings .....	19
Insulated hub .....	19; 21
Interface standard RS 422 .....	11; 24
Internal temperature .....	19
Interpolation .....	8; 13–14
Inverted signals .....	8; 10–11
IP protection class .....	20
ISO 9001 .....	20
Isolation of signals .....	25

## J

Jitter .....	9
--------------	---

## L

Level shifting .....	25
Life time, ball bearings .....	18
LED .....	9
Light alloy housing .....	18
Light emitting diode (LED) .....	9
Line driver IC .....	11; 17
Line driver transistors .....	12
Line receivers .....	24–25
Lissajous figure .....	14
Load carrying capacity of the shaft .....	18
Load current .....	10–12
Logic levels .....	10–11
LongLife® dc tachogenerators .....	16; 18; 23
Long-time stability .....	23
LowHarmonics® Sinus-Tachos .....	14–16

## M

Maritime climates .....	18
Marker pulse .....	8; 15
Mark-space ratio .....	11
Max. cable length .....	12
Max. load current .....	10–12
Max. rotational speed .....	18
Max. switching frequency .....	9
Maximum rotational speed .....	18
Metal-bodied mating connector .....	20
Min. rotational speed .....	9
Mismatch .....	24
Moment of inertia .....	21
Multiplexer (MUX) .....	15
Multi-turn encoder .....	16

## N

Noise margin .....	10–11; 15; 24–25
Number of slots .....	9

## O

Opto-ASIC .....	9
Opto-coupler inputs .....	25
Opto-electronic scanning .....	9; 15
Output signals .....	8
Overspeed switches .....	23

## P

Peak current .....	10–12
PG fitting .....	20
Phase shift (sinewave) .....	14
Power loss .....	12; 19; 24
Power supply wires .....	17
Power transistors .....	10; 12
Protection against maritime climates and tropicalization .....	18
Protection class .....	20
Pulse offset (squarewave) .....	11
Pulses per revolution .....	8
Push-pull line driver .....	12
Push-pull photoelectric receivers .....	9

## R

Reaction torque .....	21
Real-time signal acquisition .....	16; 23
Rear shaft .....	18; 31
Redundant scanning .....	9
Reference voltage (sinewave) .....	17
Reflections .....	24
Regeneration of signals .....	25
Resonant frequency .....	16; 21; 23
Reverse polarity protection .....	17
Rise time .....	11; 12
Rotational speed .....	8; 16
RS 422 interface standard .....	11; 24

## S

Safety Regulations .....	24
Sampling period .....	9
Scanning, opto-electronic .....	8
redundant .....	9; 31
Scanning electronics .....	9
Sealing .....	20
Serial number .....	31
Shaft, common .....	16; 20; 23
Shaft currents .....	18
Shaft displacement .....	21
Short circuit current limiting .....	12
Signal cable .....	24
Signal level shifting .....	25
Signal level .....	10–11
Signal regeneration .....	25
Signal to noise margin .....	10–11; 15; 24–25
Signal transmission .....	24–25
Sinewave signals .....	8; 13–14
Single channel Digital-Tachos .....	8
Sinus-Tachos (sinewave encoders) .....	8; 13
Size .....	18
Sliding earth contact .....	19
Solid shaft .....	19; 21
Spring disk couplings .....	19; 21
Spring-mass system .....	21; 23
Stainless steel housing .....	18; 31
Stator coupling .....	21
Supply voltage .....	10–11; 17
Suppression capacitors .....	17
Susceptibility to interference (EMC) .....	17
Switching frequency .....	9

## T

Temperature monitoring .....	12
Temperature range .....	19
Terminal box .....	20
Terminating resistor .....	24
Time lag .....	13
Torque arms .....	21
Torsional rigidity .....	21
Tropicalization .....	18
TTL technology .....	11
TTL technology, version R .....	11
Twin encoders .....	9; 23

## V

Version C (HTL) .....	11
Version R (TTL) .....	11
Vibration and shock resistance .....	19
Voltage regulator .....	11; 19
Voltage rise time .....	11; 12
Voltage spikes .....	17

## Z

Zero transitions .....	8; 13
------------------------	-------